

JA665



High
Durability



High
Strength

- High durability
- High scrub resistance



Suitable 



Size	Standard Rim	PR	Load				Pressure				Load Index		Tread Depth (mm)	Speed Grade	Inflated Tyre Dimation (mm)	
			KG		lbs		kPa		psi						D	B
			S	D	S	D	S	D	S	D	S	D				
12.00R24	8,5	20	4500	4125	9920	9090	900	900	130	130	160	157	14.5	K	1226	315
11R22.5	8,25	16	3000	2725	6610	6005	830	830	120	120	146	143	18	K	1054	279
11R24.5	8,25	16	3250	3000	7160	6610	830	830	120	120	149	146	18	K	1104	279
12R22.5	9.00	18	3550	3250	7825	7165	930	930	135	135	152	149	18	K	1085	300
13R22.5	9.75	18	3750	3450	8270	7610	830	830	120	120	154	151	18	K	1136	320
13R22.5	9.75	18	4000	3350	8820	7385	875	875	125	125	156	150	18	L	1136	320
13R22.5	9.75	20	4000	3350	8820	7390	900	900	130	130	156	150	18	L	1124	320
295/80R22.5	9.00	18	3550	3250	7825	7165	900	900	130	130	152	149	18.5	K	1044	298
315/80R22.5	9.00	20	4000	3650	8820	8045	850	850	125	125	156	153	17	K	1082	312

1inch=25.4mm 1kPa=0.142psi 1KG≈2.2lbs