



## JD575



- Excellent traction
- High wear-resistance



Size	Standard Rim	PR	Load				Pressure				Load Index		TreadDepth (mm)	Speed Grade	Inflated Tyre Dimension (mm)	
			KG		lbs		kPa		psi		S	D			D	B
			S	D	S	D	S	D	S	D						
205/75R17.5	6.00	14	1600	1500	3525	3315	750	750	110	110	124	122	15	L	753	205
215/75R17.5	6.00	14	1700	1600	3750	3525	700	700	100	100	126	124	15	M	773	211
215/75R17.5	6.00	16	2180	2060	4805	4540	860	860	125	125	135	133	15	L	773	211
215/75R17.5	6.00	16	2180	2060	4805	4540	860	860	125	125	135	133	15	J	773	211
235/75R17.5	6.75	16	2000	1900	4410	4190	760	760	110	110	132	130	15	M	803	233
235/75R17.5	6.75	18	2725	2575	6005	5675	860	860	125	125	143	141	15	L	803	233
225/70R19.5	6.75	12	1650	1550	3640	3415	660	660	95	95	125	123	15	L	817	226
225/70R19.5	6.75	14	1800	1700	3970	3750	760	760	110	110	128	126	15	L	817	226
245/70R19.5	7.50	12	1850	1750	4080	3860	660	660	95	95	129	127	15.5	M	845	248
245/70R19.5	7.50	14	2060	1950	4540	4300	760	760	110	110	133	131	15.5	L	845	248
245/70R19.5	7.50	16	2240	2120	4940	4675	830	830	120	120	136	134	15.5	M	845	248
245/70R19.5	7.50	18	2800	2650	6175	5840	900	900	130	130	144	142	15.5	J	845	248
265/70R19.5	7.50	14	2300	2120	5070	4675	760	760	110	110	137	134	15.5	L	873	262
265/70R19.5	7.50	16	2500	2360	5510	5205	760	760	110	110	140	138	15.5	L	873	262
265/70R19.5	7.50	18	2725	2575	6005	5675	900	900	130	130	143	141	15.5	J	873	262
285/70R19.5	8.25	14	2500	2300	5510	5070	725	725	105	105	140	137	16	L	895	283
285/70R19.5	8.25	16	2900	2725	6395	6005	850	850	125	125	145	143	16	M	895	283
285/70R19.5	8.25	16	3350	3150	7390	6945	900	900	130	130	150	148	16	K	895	283
285/70R19.5	8.25	18	3000	2800	6610	6175	900	900	130	130	146	144	16	L	895	283
295/60R22.5	9.00	18	3350	3075	7390	6780	900	900	130	130	150	147	19	L	926	292
315/60R22.5	9.75	18	3550	3150	7825	6945	900	900	130	130	152	148	20	L	950	313
315/70R22.5	9.00	16	3550	3150	7830	6940	850	850	123	123	152	148	20	M	1020	312
315/70R22.5	9.00	18	4000	3350	8820	7385	900	900	130	130	156	150	20	L	1020	312
315/70R22.5	9.00	18	3750	3350	8265	7385	900	900	130	130	154	150	20	L	1020	312
295/80R22.5	9.00	16	3350	3075	7390	6780	830	830	120	120	150	147	22	M	1050	298
295/80R22.5	9.00	16	3550	3150	7825	6945	850	850	125	125	152	148	22	M	1050	298
295/80R22.5	9.00	18	3550	3250	7825	7165	900	900	130	130	152	149	22	L	1050	298
315/80R22.5	9.00	18	4000	3350	8820	7385	850	850	123	123	156	150	22.5	L	1082	312
315/80R22.5	9.00	18	3750	3450	8270	7610	830	830	120	120	154	151	22.5	L	1082	312
315/80R22.5	9.00	20	4000	3650	8820	8050	850	850	120	120	156	153	22.5	K	1082	312

1inch=25.4mm 1kPa=0.142psi 1KG=2.2 lbs