

JD690



High
Durability



High
Strength



Excellent
Grip

- Cool running
- High wear-resistance



Suitable 



Size	Standard Rim	PR	Load				Pressure				Load Index		Tread Depth (mm)	Speed Grade	Inflated Tyre Dimention (mm)	
			KG		lbs		kPa		psi						D	B
			S	D	S	D	S	D	S	D	S	D				
7.00R16LT	5.50F	14	1320	1180	2910	2600	770	770	110	110	118	114	11.5	L	775	205
7.50R16LT	6.00G	14	1500	1320	3310	2910	770	770	110	110	122	118	12.5	L	805	215
8.25R16LT	6.50H	16	1800	1600	3970	3530	770	770	110	110	128	124	13.5	L	855	235
8.25R20	6.5	16	2430	2300	5360	5070	930	930	135	135	139	137	15	K	974	236
9.00R20	7.0	16	2800	2650	6170	5840	900	900	130	130	144	142	15.5	K	1019	259
10.00R20	7.5	16	3000	2725	6610	6010	830	830	120	120	146	143	16	K	1054	278
11.00R20	8.0	18	3550	3250	7830	7160	930	930	135	135	152	149	17.5	K	1096	293
12.00R20	8.5	18	3750	3450	8270	7610	830	830	120	120	154	151	18	K	1136	315
12.00R20	8.5	20	4000	3650	8820	8050	900	900	130	130	156	153	18	K	1136	315

1inch=25.4mm 1kPa=0.142psi 1KG≈2.2 lbs