



JY522




- High scrub resistance
- Low noise emissions
- Cool running
- Long tread life

Size	Standard	PR	Load				Pressure				Load Index		TreadDepth (mm)	Speed Grade	Inflated Tyre Dimension (mm)	
			KG		lbs		kPa		psi							
			S	D	S	D	S	D	S	D	S	D				
11R22.5	8.25	14	2800	2650	6175	5840	720	720	105	105	144	142	15.5	M	1054	279
11R22.5	8.25	16	3000	2725	6610	6010	830	830	120	120	146	143	15.5	L	1054	279
12R22.5	9.00	16	3350	3075	7390	6780	830	830	120	120	150	147	16	L	1085	300
12R22.5	9.00	18	3550	3250	7825	7165	930	930	135	135	152	149	16	K	1085	300
315/80R22.5	9.00	18	3750	3450	8270	7610	830	830	120	120	154	151	16	L	1076	312
315/80R22.5	9.00	20	4000	3650	8820	8045	850	850	125	125	156	153	16	L	1076	312



JF568



Size	Standard Rim	PR	Load				Pressure				Load Index		TreadDepth (mm)	Speed Grade	Inflated Tyre Dimension (mm)	
			KG		lbs		kPa		psi							
			S	D	S	D	S	D	S	D	S	D				
8.5R17.5	6.00	12	1450	1400	3195	3085	625	625	90	90	121	120	11	M	802	215
	6.75	14	1850	1750	4080	3860	750	750	110	110	129	127	13.5	L	842	240
9.5R17.5	6.75	16	1950	1850	4300	4080	830	830	120	120	131	129	13.5	L	842	240
	6.75	18	2725	2575	6005	5675	875	875	125	125	143	141	13.5	J	842	240
11R22.5	8.25	16	3150	2900	6940	6395	840	840	120	120	148	145	15	M	1054	279
12R22.5	9.00	16	3350	3075	7390	6780	830	830	120	120	150	147	15	L	1085	300
	9.00	18	3550	3150	7825	6945	850	850	125	125	152	148	15	L	1085	300
	6.00	14	1600	1500	3525	3315	750	750	110	110	124	122	13	M	753	205
205/75R17.5	6.00	14	1700	1600	3750	3525	700	700	100	100	126	124	12.5	M	767	211
215/75R17.5	6.00	16	2180	2060	4805	4540	860	860	125	125	135	133	12.5	L	767	211
	6.00	16	2180	2060	4805	4540	860	860	125	125	135	133	12.5	J	767	211
235/75R17.5	6.75	16	2000	1900	4410	4190	760	760	110	110	132	130	13	M	797	233
	6.75	18	2725	2575	6005	5675	860	860	125	125	143	141	13	L	797	233
225/70R19.5	6.75	12	1650	1550	3640	3415	660	660	95	95	125	123	12.5	L	811	226
	6.75	14	1800	1700	3970	3750	760	760	110	110	128	126	12.5	L	811	226
	7.50	12	1850	1750	4080	3860	660	660	95	95	129	127	13	M	839	248
	7.50	14	2060	1950	4540	4300	760	760	110	110	133	131	13	M	839	248
245/70R19.5	7.50	16	2240	2120	4940	4675	830	830	120	120	136	134	13	M	839	248
	7.50	18	2800	2650	6175	5840	900	900	130	130	144	142	13	J	839	248
	7.50	14	2300	2120	5070	4675	760	760	110	110	137	134	13.5	L	867	262
265/70R19.5	7.50	16	2500	2360	5510	5205	760	760	110	110	140	138	13.5	M	867	262
	7.50	18	2725	2575	6005	5675	900	900	130	130	143	141	13.5	J	867	262
	8.25	14	2500	2300	5510	5070	725	725	105	105	140	137	13	M	895	283
	8.25	16	3000	2800	6610	6175	900	900	130	130	146	144	13	M	895	283
285/70R19.5	8.25	16	2900	2725	6395	6005	850	850	125	125	145	143	13	M	895	283
	8.25	18	3350	3150	7390	6945	900	900	130	130	150	148	13	K	895	283
	7.50	16	2500	2300	5510	5070	830	830	120	120	140	137	13.5	M	930	255
255/70R22.5	7.50	14	2360	2120	5205	4675	760	760	110	110	138	134	13.5	M	930	255
275/70R22.5	8.25	16	3150	2900	6945	6395	900	900	130	130	148	145	14.5	M	958	275
295/60R22.5	9.00	18	3350	3075	7390	6780	900	900	130	130	150	147	14.5	L	926	292
315/60R22.5	9.75	18	3550	3150	7825	6945	900	900	130	130	152	148	14.5	L	950	313
	9.00	16	3550	3150	7830	6940	850	850	123	123	152	148	15.5	M	1014	312
	9.00	18	4000	3350	8820	7385	900	900	130	130	156	150	15.5	L	1014	312
315/70R22.5	9.00	18	3750	3350	8265	7385	900	900	130	130	154	150	15.5	L	1014	312
	9.00	16	3350	3075	7390	6780	830	830	120	120	150	147	16	M	1044	298
295/80R22.5	9.00	16	3550	3150	7825	6945	850	850	125	125	152	148	16	M	1044	298
	9.00	18	3550	3250	7825	7165	900	900	130	130	152	149	16	M	1044	298
315/80R22.5	9.00	18	4000	3350	8820	7385	850	850	123	123	156	150	16.5	L	1076	312
	9.00	18	3750	3450	8270	7610	830	830	120	120	154	151	16.5	L	1076	312
	9.00	20	4000	3650	8820	8050	850	850	120	120	156	153	16.5	L	1076	312

1inch=25.4mm 1kPa=0.142psi 1KG=2.2 lbs