



JY601




- Cool running
- High durability

Size	Standard Rim	Pr	Load				Pressure				Load Index		TreadDepth (mm)	Speed Grade	Inflated Tyre Dimension (mm)	
			kg		lbs		kpa		psi		S	D			D	B
			S	D	S	D	S	D	S	D						
7.00R16LT	5.50F	12	1215	1060	2680	2340	670	670	97	97	115	110	11.5	L	775	205
7.00R16LT	5.50F	14	1320	1180	2910	2600	770	770	110	110	118	114	11.5	L	775	205
7.50R16LT	6.00G	12	1400	1250	3085	2755	670	670	97	97	120	116	12.5	K	805	215
7.50R16LT	6.00G	14	1500	1320	3310	2910	770	770	110	110	122	118	12.5	L	805	215
8.25R16LT	6.50H	14	1700	1500	3750	3310	670	670	97	97	126	122	12.5	L	855	235
8.25R16LT	6.50H	16	1800	1600	3970	3530	770	770	110	110	128	124	12.5	L	855	235
8.25R20	6.50	16	2430	2300	5360	5070	930	930	135	135	139	137	13.5	K	974	236
9.00R20	7.00	14	2575	2430	5680	5360	790	790	115	115	141	139	15	K	1019	259
9.00R20	7.00	16	2800	2650	6170	5840	900	900	130	130	144	142	15	K	1019	259
10.00R20	7.50	16	3000	2725	6610	6010	830	830	120	120	146	143	16	K	1054	278
10.00R20	7.50	18	3250	3000	7165	6610	930	930	135	135	149	146	16	K	1054	278
11.00R20	8.00	16	3350	3075	7385	6780	830	830	120	120	150	147	16.5	K	1085	293
11.00R20	8.00	18	3550	3250	7830	7170	930	930	135	135	152	149	16.5	K	1085	293
12.00R20	8.50	18	3750	3450	8270	7610	830	830	120	120	154	151	17	K	1125	315
12.00R20	8.50	20	4000	3650	8820	8050	900	900	130	130	156	153	17	K	1125	315
11R22.5	8.25	14	2800	2650	6175	5840	720	720	105	105	144	142	16	M	1054	279
11R22.5	8.25	16	3150	2900	6945	6395	840	840	120	120	148	145	16	M	1054	279
11R24.5	8.25	14	3000	2725	6610	6005	720	720	105	105	146	143	16	L	1104	279
11R24.5	8.25	16	3250	3000	7160	6610	830	830	120	120	149	146	16	M	1104	279
12R22.5	9.00	16	3350	3075	7390	6780	830	830	120	120	150	147	16.5	L	1085	300
12R22.5	9.00	18	3550	3150	7825	6945	850	850	125	125	152	148	16.5	K	1085	300
13R22.5	9.75	18	3750	3350	8270	7390	850	850	125	125	154	150	16	L	1124	320
13R22.5	9.75	20	4000	3350	8820	7390	900	900	130	130	156	150	16	J	1124	320
295/80R22.5	9.00	16	3550	3150	7825	6945	850	850	125	125	152	149	17.5	M	1050	298
295/80R22.5	9.00	18	3550	3250	7825	7165	900	900	130	130	152	149	17.5	L	1050	298
315/80R22.5	9.00	16	3450	3150	7605	6945	760	760	110	110	151	148	16	L	1076	312
315/80R22.5	9.00	18	3750	3450	8270	7610	830	830	120	120	154	151	16	L	1076	312
315/80R22.5	9.00	20	4000	3650	8820	8045	850	850	125	125	156	153	16	K	1076	312



JY602



- Cool running
- High durability

Size	Standard Rim	PR	Load				Pressure				Load Index		TreadDepth (mm)	Speed Grade	Inflated Tyre Dimension (mm)	
			KG		lbs		kPa		psi							
			S	D	S	D	S	D	S	D	S	D				
6.50R16LT	5.50F	12	1060	925	2340	2040	670	670	97	97	110	105	10.5	L	185	750
12.00R20	8.50	18	3750	3450	8270	7610	830	830	120	120	154	151	17	K	315	1125
12.00R20	8.50	20	4000	3650	8820	8050	900	900	130	130	156	153	17	K	315	1125
295/80R22.5	9.00	18	3550	3250	7825	7165	900	900	130	130	152	149	16	L	298	1044

1inch=25.4mm 1kPa=0.142psi 1KG=2.2 lbs



JY719



- Excellent traction
- High scrub resistance
- Cut resistant

Size	Standard Rim	PR	Load				Pressure				Load Index		TreadDepth (mm)	Speed Grade	Inflated Tyre Dimension (mm)	
			KG		lbs		kPa		psi		S	D			D	B
			S	D	S	D	S	D	S	D						
7.00R16LT	5.50F	14	1320	1180	2910	2600	770	770	112	112	118	114	14	L	775	205
7.50R16LT	6.00G	14	1500	1320	3305	2910	770	770	112	112	122	118	15.5	L	811	215
8.25R16	6.50H	14	1700	1500	3750	3310	670	670	97	97	126	122	15.5	L	865	235
8.25R16	6.50H	16	1800	1600	3970	3525	770	770	110	110	128	124	15.5	L	865	235
8.25R20	6.50	16	2430	2300	5360	5070	930	930	135	135	139	137	17	K	974	236
9.00R20	7.00	14	2575	2430	5660	5340	790	790	115	115	141	139	18	K	1030	259
9.00R20	7.00	16	2800	2650	6170	5840	900	900	130	130	144	142	18	K	1030	259
9.5R17.5	6.75	18	2725	2565	6005	5575	875	875	125	125	143	141	17	K	850	240
10.00R20	7.50	16	3000	2725	6605	6010	830	830	120	120	146	143	19	K	1065	278
10.00R20	7.50	18	3250	3000	7160	6610	930	930	135	135	149	146	19	K	1065	278
12.00R24	8.50	18	4250	3875	9370	8540	830	830	120	120	158	155	20	K	1238	315
12.00R24	8.50	20	4500	4125	9920	9090	900	900	130	130	160	157	20	K	1238	315
265/70R19.5	7.50	18	2725	2565	6005	5575	900	900	130	130	143	141	15	K	867	262

1inch=25.4mm 1kPa=0.142psi 1KG=2.2 lbs