

HOME - PRODUCTS - REGIONAL

JY711



High
Speed



High
Durability



High
Strength



Excellent
Grip

- Cool running
- Long tread life
- Excellent traction
- High scrub resistance

Suitable



View in 0° 30° 90°

Origin		Size	PR	LI/ SS	Standard Rim	Max. Load				Pressure				Tread Depth (mm)	Overall Diameter (mm)	Section Width (mm)	
						(kgs)		(lbs)		(kPa)		(PSI)					
CN	VN					S	D	S	D	S	D	S	D				
•		11R22.5	16	146/143	L	8.25	3000	2725	6610	6010	830	830	120	120	21.5	1059	279
•		11R22.5	16	148/145	L	8.25	3150	2900	6940	6395	850	850	123	123	21.5	1059	279
•		12R22.5	18	152/149	K	9.00	3550	3250	7825	7165	930	930	135	135	22.5	1096	300
•		13R22.5	18	154/151	K	9.75	3750	3450	8270	7605	830	830	120	120	23.5	1124	320
•		315/80R22.5	20	156/153	L	9.00	4000	3650	8820	8045	850	850	125	125	24.5	1076	312

S=Single D=Dual; 1 inch=25.4mm 1kPa=0.142psi 1KG=2.2lbs