

LT (SUV / VAN / Light Truck)

Light Truck / Camioneta / Comerciais / Camionnette



Mud Terrain

ROAD VENTURE MT51



English

- Mild MT for mine and mountain climbing
- Improved on-road driving performance
- Stone ejector and mud cleaning performance



Español

- Leve MT para conducción en montaña
- Rendimiento de conducción sobre carretera mejorado
- Ejector de piedras y sistema de limpieza de barro



Português

- Pneu MT para terrenos montanhosos
- Desempenho melhorado para condições de pistas pavimentadas
- Ejetor de pedras e auto limpeza de lama de alto desempenho



Français

- Pneu mixte pour franchissement
- Performance sur route améliorée
- Ejecte les pierres, évacue la boue



reddot

MT51

Rim	Tire Size	Measuring Rim Width	Approved Rim Width	Max. Air Pressure		Max. Load		Section Width		Overall Diameter		Tread Depth		Static Loaded Radius	Rolling Circumference	Rim Protector			
				bar	psi	kg	lbs	mm	inch	mm	inch	mm	x/32"				mm	mm	
Black Sidewall																			
18"	LT 265/60 R18	10	S	119Q	8.0	7.5 - 9.5	5.5	80	1360	3000	272	10.7	781	30.7	14.5	18.3	355	2382	o
17"	LT 285/70 R17	10	S	121Q	8.5	7.5 - 9.0	5.5	80	1450	3195	292	11.5	838	33.0	14.5	18.3	374	2556	o
	LT 275/65 R17	10	S	121Q	8.0	7.5 - 9.5	5.5	80	1450	3195	279	11.0	796	31.3	14.5	18.3	358	2428	o
16"	LT 265/65 R17	10	S	120Q	8.0	7.5 - 9.5	5.5	80	1400	3085	272	10.7	782	30.8	14.5	18.3	352	2385	o
	LT 265/70 R17	10	S	121Q	8.0	7.0 - 8.5	5.5	80	1450	3195	272	10.7	810	31.9	14.5	18.3	363	2471	o
15"	LT 245/70 R17	10	S	119Q	7.0	6.5 - 8.0	5.5	80	1360	3000	248	9.8	782	30.8	14.5	18.3	352	2385	o
	LT 225/70 R17	08	S	110Q	6.5	6.0 - 7.5	4.5	65	1060	2335	228	9.0	754	29.7	14.5	18.3	342	2300	o
16"	LT 315/75 R16	10	S	127Q	8.5	8.0 - 11.0	4.5	65	1750	3860	313	12.3	884	34.8	14.5	18.3	389	2696	o
	LT 305/70 R16	10	S	124Q	9.0	8.0 - 9.5	4.5	65	1600	3525	311	12.2	840	33.1	14.5	18.3	372	2562	o
	LT 285/75 R16	10	S	126Q	8.0	7.5 - 9.0	5.5	80	1700	3750	286	11.3	840	33.1	14.5	18.3	372	2562	o
	LT 265/70 R16	08	S	117Q	8.0	7.0 - 8.5	4.5	65	1285	2835	272	10.7	784	30.9	14.5	18.3	350	2391	o
	LT 265/75 R16	10	S	123Q	7.5	7.0 - 8.0	5.5	80	1550	3415	267	10.5	810	31.9	14.5	18.3	361	2471	o
	LT 255/70 R16	08	S	115Q	7.5	6.5 - 8.0	4.5	65	1215	2680	260	10.2	770	30.3	14.5	18.3	345	2349	o
	LT 245/70 R16	10	S	118Q	7.0	6.5 - 7.5	5.5	80	1320	2910	248	9.8	756	29.8	14.5	18.3	340	2306	o
	LT 245/75 R16	10	S	120Q	7.0	6.5 - 8.0	5.5	80	1380	3042	248	9.8	780	30.7	14.5	18.3	349	2379	o
LT 235/85 R16	10	S	120Q	6.5	6.0 - 7.5	5.5	80	1380	3042	235	9.3	812	32.0	14.5	18.3	361	2477	o	
																			D
LT 225/75 R16	10	S	115Q	6.0	6.0 - 7.0	5.5	80	1215	2680	223	8.8	750	29.5	14.5	18.3	337	2288	o	
																			D
15"	33X12.5 R15 LT	06	S	108Q	10.0	8.5 - 11.0	2.4	35	1000	2205	318	12.5	832	32.8	14.5	18.3	366	2538	o
	32X11.5 R15 LT	06	S	113Q	9.0	8.0 - 10.0	3.4	50	1150	2535	290	11.4	807	31.8	14.5	18.3	357	2461	o
31X10.5 R15 LT	06	S	109Q	8.5	7.0 - 9.0	3.4	50	1030	2270	268	10.6	781	30.7	14.5	18.3	347	2382	o	
																			D
LT 235/75 R15	08	S	110Q	6.5	6.0 - 7.0	4.5	65	1060	2335	235	9.3	739	29.1	14.5	18.3	330	2254	o	
																			D