



TR688



FEATURE:

- Center rib plus open shoulder design
- Deep OTD
- Strong casing package

ADVANTAGE:

- Provides good traction in wet/dry conditions
- Long tread wear life
- Increased casing toughness

BENEFIT:

- Good traction for handling
- Good mileage
- Improved retreadability



TTR-A11



FEATURE:

- Optimized pattern design
- Wide tread width design
- Strong closed shoulder ribs

ADVANTAGE:

- Wear performance focused for all position tire under regional haul operation
- Additional cap gum volume on tread gives big contact patch
- Maintains shoulder rib toughness during regional haul operation.

BENEFIT:

- Mileage and traction
- Extra mileage and traction
- Even wear and mileage

Size	LI/SS	PR	Rim size	Rim allowance	Inflated Section width mm	Overall diameter mm	Radius under load mm	Load capacity kg/lbs				IP		OTD mm
								Single	Dual	kPa	psi	kPa	psi	
9.00R20	141/139L	14	7.00	7.00T,7.50	259	1019	471	2575	5675	2430	5355	790	115	16.0
9.00R20	144/142K	16	7.00	7.00T,7.50	259	1019	471	2800	6175	2650	5840	900	130	16.0
11R22.5	144/142M	14	8.25	7.50	279	1054	491	2800	6175	2650	5840	720	105	18.0
11R22.5	146/143M	16	8.25	7.50	279	1054	491	3000	6610	2725	6005	830	120	18.0
11R22.5	148/144M	16+	8.25	7.50	279	1054	491	6610	5800			Single: 120 Dual: 110		18.0
12R22.5	150/147L	16	9.00	8.25	300	1085	504	3350	7390	3075	6780	830	120	20.0
12R22.5	152/149K	18	9.00	8.25	300	1085	504	3550	7830	3250	7160	930	135	20.0
11R24.5	146/143M	14	8.25	7.50	279	1104	516	3000	6610	2725	6005	720	105	18.0
11R24.5	149/146M	16	8.25	7.50	279	1104	516	3250	7160	3000	6610	830	120	18.0
295/80R22.5	152/148M	16	9.00	8.25	298	1044	487	3550	7825	3150	6945	850	125	18.0
295/80R22.5	152/149L	18	9.00	8.25	298	1044	487	3550	7825	3250	7160	900	130	18.0
315/80R22.5	151/148M	16	9.00	9.75	312	1076	500	3450	7610	3150	6940	760	110	20.0
315/80R22.5	154/151M	18	9.00	9.75	312	1076	500	3750	8270	3450	7610	830	120	20.0
315/80R22.5	157/154L	20	9.00	9.75	312	1076	500	4125	9090	3750	8270	900	130	20.0
295/75R22.5	144/141M	14	9.00	8.25	298	1014	474	2800	6175	2575	5675	760	110	18.0
295/75R22.5	146/143M	16	9.00	8.25	298	1014	474	3000	6610	2725	6005	830	120	18.0

Size	LI/SS	PR	Rim size	Rim allowance	Inflated Section width mm	Overall diameter mm	Radius under load mm	Load capacity kg/lbs				IP		OTD mm
								Single	Dual	kPa	psi	kPa	psi	
12R22.5	150/147L	16	9.00	8.25	300	1085	504	3350	7390	3075	6780	830	120	17.5
12R22.5	152/149K	18	9.00	8.25	300	1085	504	3550	7830	3250	7160	930	135	17.5
325/95R24	162/160K	18	9.00	9.00	325	1228	568	4750	10500	4500	9920	830	120	17.0
325/95R24	164/162J	20	9.00	9.00	325	1228	568	5000	11000	4750	10500	900	130	17.0
325/95R24	162/160K	22	9.00	9.00	325	1228	568	4750	10500	4500	9920	830	120	17.0
295/80R22.5	152/148M	16	9.00	8.25	298	1044	487	3550	7825	3150	6945	850	125	17.5
295/80R22.5	152/149M	18	9.00	8.25	298	1044	487	3550	7825	3250	7160	900	130	17.5

TR668

Size	LI/SS	PR	Rim size	Rim allowance	Inflated Section width mm	Overall diameter mm	Radius under load mm	Load capacity kg/lbs		IP		OTD mm
								Single	Dual	kPa	psi	
7.50R15TR	136/134J	18	6.00	5.50,6.50	215	808	372	2240 4940	2120 4675	830 120	12.5	
7.50R16LT	105/101L	6	6.00G	5.50F,6.50H	215	805	375	925 2040	825 1820	350 50	12.5	
7.50R16LT	112/107L	8	6.00G	5.50F,6.50H	215	805	375	1120 2470	975 2150	460 65	12.5	
7.50R16LT	122/118L	14	6.00G	5.50F,6.50H	215	805	375	1500 3305	1320 2910	770 110	12.5	
7.50R16LT	125/121L	16	6.00G	5.50F,6.50H	215	805	375	1650 3640	1450 3195	870 126	12.5	
8.25R16LT	110/105M	6	6.50H	6.00G,6.50	235	855	397	1060 2335	925 2040	320 45	13.0	
8.25R16LT	126/122M	14	6.50H	6.00G,6.50	235	855	397	1700 3750	1500 3305	670 97	13.0	
8.25R16LT	128/124M	16	6.50H	6.00G,6.50	235	855	397	1800 3970	1600 3525	770 112	13.0	
8.25R16LT	132/128L	18	6.50H	6.00G,6.50	235	855	397	2000 4410	1800 3970	870 126	13.0	
8.25R20	136/134L	14	6.50	6.50T,7.00,7.00T	236	974	452	2240 4940	2120 4675	830 120	14.0	
8.25R20	139/137L	16	6.50	6.50T,7.00,7.00T	236	974	452	2430 5355	2300 5070	930 135	14.0	
9.00R20	141/139L	14	7.00	7.00T,7.50	259	1019	471	2575 5675	2430 5355	790 115	15.5	
9.00R20	141/139K	14	7.00	7.00T,7.50	259	1019	471	2575 5675	2430 5355	790 115	15.5	
9.00R20	144/142K	16	7.00	7.00T,7.50	259	1019	471	2800 6175	2650 5840	900 130	15.5	
9.00R20	144/142L	16	7.00	7.00T,7.50	259	1019	471	2800 6175	2650 5840	900 130	15.5	
10.00R20	146/143K	16	7.50	7.50V,8.00	278	1054	486	3000 6610	2725 6005	830 120	16.5	
10.00R20	146/143L	16	7.50	7.50V,8.00	278	1054	486	3000 6610	2725 6005	830 120	16.5	
10.00R20	149/146K	18	7.50	7.50V,8.00	278	1054	486	3250 7160	3000 6610	930 135	16.5	
10.00R20	149/146L	18	7.50	7.50V,8.00	278	1054	486	3250 7160	3000 6610	930 135	16.5	
11.00R20	143/141K	12	8.00	8.50,8.00V	293	1085	499	2725 6005	2575 5675	620 90	17.0	
11.00R20	150/147K	16	8.00	8.50,8.00V	293	1085	499	3350 7390	3075 6780	830 120	17.0	
11.00R20	150/147L	16	8.00	8.50,8.00V	293	1085	499	3350 7390	3075 6780	830 120	17.0	
11.00R20	152/149K	18	8.00	8.50,8.00V	293	1085	499	3550 7830	3250 7160	930 135	17.0	
11.00R20	152/149L	18	8.00	8.50,8.00V	293	1085	499	3550 7830	3250 7160	930 135	17.0	
12.00R20	152/149K	16	8.50	8.50V,9.00	315	1125	516	3550 7830	3250 7160	760 110	17.5	
12.00R20	154/151K	18	8.50	8.50V,9.00	315	1125	516	3750 8270	3450 7610	830 120	17.5	
12.00R20	154/151L	18	8.50	8.50V,9.00	315	1125	516	3750 8270	3450 7610	830 120	17.5	
12.00R20	154/151K	18	8.50	8.50V,9.00	315	1125	516	3730 8210	3270 7200	840 120	17.5	
12.00R20	156/153K	20	8.50	8.50V,9.00	315	1125	516	4000 8820	3650 8050	900 131	17.5	
12.00R20	158/155J	22	8.50	8.50V,9.00	315	1125	516	4250 9370	3875 8540	970 141	17.5	
12.00R20	158/155L	22	8.50	8.50V,9.00	315	1125	516	4250 9370	3875 8540	970 141	17.5	
9R22.5	136/134L	14	6.75	6.00,7.50	229	974	457	2240 4940	2120 4675	830 120	14.0	
11R22.5	144/142M	14	8.25	7.50	279	1054	491	2800 6175	2650 5840	720 105	16.5	
11R22.5	146/143M	16	8.25	7.50	279	1054	491	3000 6610	2725 6005	830 120	16.5	
11R22.5	148/145L	16+	8.25	7.50	279	1054	491	3150 6940	2900 6395	850 125	16.5	
12R22.5	143/141L	12	9.00	8.25	300	1085	504	2725 6005	2575 5675	620 90	17.0	
12R22.5	150/147L	16	9.00	8.25	300	1085	504	3350 7390	3075 6780	830 120	17.0	
12R22.5	152/149K	18	9.00	8.25	300	1085	504	3550 7830	3250 7160	930 135	17.0	
13R22.5	156/153L	18	9.75	9.00	320	1124	521	4000 8820	3650 8050	875 127	17.5	
13R22.5	156/153L	20	9.75	9.00	320	1124	521	4000 8820	3650 8050	930 135	17.5	
11R24.5	146/143M	14	8.25	7.50	279	1104	516	3000 6610	2725 6005	720 105	16.5	
11R24.5	149/146M	16	8.25	7.50	279	1104	516	3250 7160	3000 6610	830 120	16.5	
295/80R22.5	152/148L	16	9.00	8.25	298	1044	487	3550 7825	3150 6945	850 125	17.5	
295/80R22.5	152/149L	18	9.00	8.25	298	1044	487	3550 7825	3250 7160	900 130	17.5	
315/80R22.5	154/151M	18	9.00	9.75	312	1076	500	3750 8270	3450 7610	830 120	17.5	
315/80R22.5	157/154L	20	9.00	9.75	312	1076	500	4125 9090	3750 8270	900 130	17.5	
315/80R22.5	161/157K	20	9.00	9.75	312	1076	500	4625 10200	4125 9090	900 130	17.5	

• LT sizes available



TR668



- Mileage
- Safety
- Wear

FEATURE:

- Classic mixed pattern designed for regional-mixed operation
- Enhanced casing package

ADVANTAGE:

- An all round pattern with wear performance and traction
- Increased casing toughness

Benefit:

- Good mileage and traction
- Good retreadability